

KYTOLA FLOWMETERS

MODEL E

1st February 1996 (Issue No. 8)



SPECIFICATIONS

Accuracy : +/-5% of range
 Pressure Drop : Dependent upon range
 (available on request)
 Operating Pressure : 30 Barg (435 Psig)
 Operating Temperature : 75°C (165°F)

OPTIONS

- Calibration for non-standard gases or liquids
- Special scales markings or ranges
- Multitube units
- Constant flow regulator
- Connection nipples
- Hand knob for needle control valve
- Viton O-ring seals

Model	Range	Scale	Options
-------	-------	-------	---------

n

K
H

H
V
O

Number of Metering Tubes
Single tube model
Multi-tube model (n = 2 -12)

Plug and valve material
Nylon
316-SS

Hand Knob
Viton Seals
Without Valve

Model	Range Code	Scale Size	Water l/min	Air* ln/min	Price £
EK	4A	1/4" BSPP	1.0	36	56.65
	4B			20	
	5C		2.4		
	5D		6.0		
	5E			45	
	5F			90	
EH	4A	1/4" BSPP	1.0	36	79.45
	4B			20	
	5C		2.4		
	5D		6.0		
	5E			45	
	5F			90	

*20°C, 101.3Kpa (68°F)

OPTIONS	
Item	Price (£)
Hand Knob	8.30
Viton Seals	6.15
Without Valve	-